





## **Adhesive & Silicones**

Our Hygienic Wall Cladding can be fully bonded to most wall substrates using our Two Part Polyurethane Adhesive. Brickwork and block work – existing ceramic tiles – plasterboard and plywood using 5mm square notched trowel applied 100% cover.

Two Part Polyurethane : 8.0 kilo for 3050mm x 1220mm sheets  
Two Part Polyurethane : 6.5 kilo for 2440mm x 1220mm sheets

We also offer our Single Part Acrylic Adhesive for using on plasterboard and plywood. We recommend wall to be unbonded PVA roller applied before using Single Part Acrylic Adhesive. Single Part Acrylic Adhesive can be 3mm square notched trowel applied 100% cover.

Single Part Acrylic Adhesive : 12 kilo will install approx 3no 2440mm x 1220mm sheets  
(using 3mm notch on smooth walls)

White Food Grade Silicone Seal White. Is the choice for sealing around all abutments to finish off any install when using Hygienic Wall Cladding in white.

## **Stainless Steel Wall Cladding**

We have found in 99.9% of industrial and commercial kitchen refits the requirement for Stainless Steel Wall Protection for behind all cook lines.

Also for protection for pillar corners and areas where trolleys are in use.

We can bespoke your requirements and provide all trims and profiles to protect your business.

Stainless Steel Joint Trims

Stainless Steel Start & Finish Trims

Stainless Steel Corner Protectors & Angle any dimension

All Stainless Steel sheets cut to size standard width of sheet 1200mm

Please call if you require any assistance.



## **Multip plank Fast Track System**

We have a fast Hygienic Wall System which can be installed single handed and can make one large room into two in no time.

35mm hollow square section panels 500mm wide with a hygienic white finish to both sides simply fix track to floor and ceiling then slide panels in and knock together – job done.

This product has so many advantages as it can be put up for temporary or permanent installs and has found a slot in the market for temporarily closing off of work areas while refurbishments take place.

Multip plank hollow section is ideal for concealing cables and pipe work.

Doors and windows can be supplied if required, please call if you require further information.

## **GRP Glasbord PIF & FXE Wall & Ceiling Panels**

Glasbord (FRP) Fibreglass Reinforced Plastic is designed and engineered to be extremely tough. Highly resistant to scratches, abrasion and staining. Ideal in applications where conditions are harsh and hygiene is paramount.

Glasbords Entire Panel is moisture resistant. It does not support mould or mildew and meets class 3 class 0 fire ratings.

Ideal installs : breweries – laboratories – warehouses – kitchens – supermarkets – processing plants.

Panel Sizes: 3050mm x 1220mm x 2.3mm White Embossed PIF  
2440mm x 1220mm x 2.3mm White Embossed PIF Class 3 FR

Adhesive and trims all in white.

## **Tools & Accessories**

Thermoformers – call for quotes

Wall Panel Rollers

Mozart Weld Trimming Tool

Trim Cutters

5mm – 3mm Notched Trowels

Welding Guns

Mixing Paddles

Double-Sided Foam Welding Tape 50mm x 2mm x 251m roll

White Weld Rod Coils

Food Safe White Silicone

Wafer Head Screws